


# OneConnect™ OCe10102-F

## High-performance 10Gbps FCoE Converged Network Adapter

**SIMPLIFIED  
NETWORKING,  
TRUSTED SAN  
INTEROPERABILITY  
AND INCREASED  
BUSINESS  
AGILITY**



### Overview

The Emulex OCe10102-F is a high-performance 10Gbps Fibre Channel over Ethernet (FCoE) adapter that consolidates traffic for networking, Fibre Channel and FCoE storage. A member of the Emulex OneConnect™ Universal Converged Network Adapter (UCNA) family, the OCe10102-F FCoE adapter supports a common 10 Gigabit Ethernet (10GbE) infrastructure for networking and storage, reducing capital expense (CapEx) for adapters, switches and cables, and operational expense (OpEx) for power, cooling and IT administration.

### Optimized Network and Storage Connectivity

#### FCoE offload

The OCe10102-F FCoE adapter supports FCoE offload using the same field-proven Emulex drivers that work with Emulex LightPulse® Fibre Channel Host Bus Adapters (HBAs) and CNAs.

#### 10 Gigabit Ethernet offload

New multi-core server platforms, server virtualization and high-demand applications are driving the need for low-latency, high-bandwidth networks. The OCe10102-F adapter meets these requirements with full 10GbE network performance using an 8-lane PCI Express Gen 2 architecture and support for stateless TCP/IP and TCP Chimney offloads.

#### Boot from LAN/SAN

Fibre Channel SAN and Preboot eXecution Environment (PXE) boot support make the OCe10102-F an ideal solution for blade servers and other diskless deployments.

### Simplified Management

#### OneCommand Manager application

The OneCommand Manager application provides centralized management of Emulex One Connect UCNAs and LightPulse HBAs and CNAs throughout the data center from a centralized management console. The OneCommand Manager application provides a graphical user interface (GUI) and a scriptable command line user interface (CLI), which drives administration efficiency.

### Key Features

#### One platform for network and storage connection

- 10Gbps Ethernet and FCoE offload
- Simplifies I/O hardware choices for IT managers

#### Superior performance

- FCoE offload
- TCP/IP stateless offloads
- TCP Chimney offload

#### Energy-efficient design

- Industry-leading performance per watt
- Complements data center “green” initiatives

#### Easy to deploy and manage with OneCommand Manager application

- One management console for network and storage
- Integrated management of UCNAs and HBAs
- Over 7 million ports administered with Emulex management software

### Key Benefits

#### Maximum return on investment

- Converges network and storage I/O with high-performance 10GbE connectivity
- One network infrastructure reduces CapEx
- One management console reduces OpEx
- Leverages existing IT investments

#### Optimized for server virtualization with vEngine™ technology

- More virtual machines (VMs) per server

#### Enterprise-ready

- Hardware parity, CRC, ECC and other advanced error checking
- Backed by field proven Emulex reliability and support



OneConnect™



OneCommand™

# OneConnect™ OCe10102-F

High-performance 10Gbps FCoE Converged Network Adapter



## SPECIFICATIONS

### Quality of service

Using the OneCommand™ Manager application, administrators can allocate portions of the 10Gb Ethernet bandwidth to network or storage traffic.

### Streamlined installation

A single installation of drivers and applications for Windows servers eliminates multiple reboots and ensures that each component is installed correctly and OneConnect UCNAs are ready to use.

### Highest Performance and Reliability

#### Enterprise-ready

Leveraging ten generations of advanced, field-proven HBA technology, the Emulex OneConnect family meets the robust interoperability and reliability requirements of corporate data centers.

#### More virtual machines per server with vEngine technology

Protocol offloads for TCP/IP and FCoE enable more VMs per server, providing greater cost savings for server virtualization.

#### Greener data centers

The Emulex OneConnect™ UCNA platform delivers industry-leading performance and scalability per watt, reducing requirements for power and cooling. Protocol offload enables efficient use of computing resources, supports more VMs per CPU, and reduces the number of servers required to support data center demands.

#### Advanced error checking

End-to-end data protection with hardware parity, CRC, ECC and other advanced error checking and correcting ensure that data is safe from corruption.

### Standards

- ANSI INCITS T11 FC-BB-5 2.0, FC-PI-2, FC-GS-4, FC-TAPE, and FCP-3
- PCI Express base spec 2.0
- PCI Bus Power Management Interface, rev. 1.2, Advanced Error Reporting (AER)
- IEEE 802.3ae (10GBASE Ethernet Ports)
- IEEE 802.1q (Virtual LANs)
- IEEE 802.3ad (Link Aggregation)
- IEEE 802.3x (Flow Control)
- IEEE 802.1p (Quality/Class of Service)
- IEEE 802.1Qaz (Enhanced Transmission Selection)
- IEEE 802.1Qaz (Data Center Bridging Capabilities Exchange)
- IEEE 802.1Qbb (Priority-based Flow Control)
- IEEE 802.1ab (Link Layer Discovery Protocol)
- PHP hot plug-hot swap

### Architecture

- Dual-channel, 10Gb/s Ethernet Link speed
- PCIe Express 2.0 (x8, 5GT/s), MSI-X support
- Integrated data buffer and code space memory

### FCoE Features

- Common driver for UCNAs and HBAs
- 64 N\_Port ID Virtualization (NPIV) interfaces (total for adapter)
- Support for FIP and FCoE Ether Types
- Fabric Provided MAC Addressing (FPMA) support
- 1024 concurrent port logins (RPIs)
- 1024 active exchanges (XRIs) per port

### Ethernet Features

- IPv4/IPv6 TCP, UDP checksum offload; Large Send Offload(LSO); Large Receive Offload; Receive Side Scaling (RSS); IPv4 TCP Chimney Offload
- VLAN insertion and extraction
- Jumbo frames up to 8000 Bytes
- Preboot eXecution Environment (PXE) 2.0 network boot support
- Interrupt coalescing
- Load balancing and failover support including adapter fault tolerance (AFT), switch fault tolerance (SFT), adaptive load balancing (ALB), teaming support and IEEE 802.3ad

### Comprehensive OS Support

- Windows Server
- VMware ESX
- Red Hat Enterprise Linux Server
- Novell SUSE® Linux Enterprise Server
- Oracle Solaris

### Hardware Environments

- x86, x64 servers
- Sun SPARC servers

### Interconnect

- Copper
  - SFP+ Direct Attached Twin-Ax Copper interface
  - Standards compliant passive copper cables up to 5m and active copper cables up to 10m
- Optical
  - Optics: 10GBASE-SR short wave lasers with LC type connector supported up to 100m

### Physical Dimensions

- Low profile with standard bracket
- (low-profile bracket available)

### Environmental Requirements

- Operating temperature: 0° to 55° C (32° to 131° F)
- Storage temperature: -40° to 70° C (-40° to 158° F)
- Relative humidity: 5% to 95% non-condensing

### Agency Approvals

- Class 1 Laser Product per DHHS 21CFR (J) and EN60825-1
- UL recognized to UL 60950-1 2nd edition
- CUR recognized to CSA22.2, No. 60950-1-07
- Bauart-certified to EN60950-1 2nd edition
- FCC Rules, Part 15, Class A
- ICES-003, Class A
- EMC Directive 2004/108/EEC (CE Mark)
  - EN55022, Class A
  - EN55024
- Australian EMC Framework (C-Tick Mark)
  - AS/NZS CISPR22, Class A
- VCCI (Japan), Class A
- KCC (Korea), Class A
- BSMI (Taiwan), Class A
- EU RoHS Compliant (Directive 2002/95/EC)
- China RoHS Compliant

### Ordering Information

- **OCe10102-FM**
  - Dual-channel, 10GBase-SR (short reach optical)
- **OCe10102-FX**
  - Dual-channel, 10GBase-CR (direct attach copper)

**World Headquarters** 3333 Susan Street, Costa Mesa, CA 92626 +1 714 662 5600  
**Wokingham, UK** +44 (0) 118 977 2929 | **Munich, Germany** +49 (0) 89 97007 177  
**Paris, France** +33 (0) 158 580 022 | **Beijing, China** +86 10 68499547  
**Tokyo, Japan** +81 3 5325 3261 | **Bangalore, India** +91 80 40156789

Emulex Connects™ Servers, Storage and People

[twitter.com/emulex](https://twitter.com/emulex) [friendfeed.com/emulex](https://www.facebook.com/emulex) [bit.ly/emulexlinks](https://www.linkedin.com/company/emulex) [bit.ly/emulexfb](https://www.youtube.com/emulex)

**EMULEX®**

[www.emulex.com](http://www.emulex.com)

©2011 Emulex, Inc. All rights reserved. This document refers to various companies and products by their trade names. In most, if not all cases, their respective companies claim these designations as trademarks or registered trademarks. This information is provided for reference only. Although this information is believed to be accurate and reliable at the time of publication, Emulex assumes no responsibility for errors or omissions. Emulex reserves the right to make changes or corrections without notice. This report is the property of Emulex and may not be duplicated without permission from the Company.