





LightPulse® LPe12000/LPe12002

8Gb/s Fibre Channel PCIe 2.0 Host Bus Adapter



**UNPARALLELED
MANAGEABILITY,
RELIABILITY,
PERFORMANCE
AND EASE OF
DEPLOYMENT**



LPe12000/LPe12002

Streamlined installation and management, unrivaled scalability, and industry-leading virtualization support make the single-channel Emulex LightPulse LPe12000 and dual-channel LPe12002 Fibre Channel host bus adapters (HBA) ideal solutions for enterprise, mixed-OS and virtual server environments.

Proven Design, Architecture and Interface

Emulex LightPulse HBAs' highly integrated processor design minimized onboard components to improve host performance and efficiency. Advanced error-checking features ensure the integrity of block data as it traverses the SAN. Emulex's firmware-based architecture enables feature and performance upgrades without costly hardware changes. The unique Service Level Interface (SLI™) allows use of a common driver across all models of Emulex HBAs on a given OS platform. Installation and management facilities are designed to minimize server reboots and further simplify deployment.

Powerful Management Software for Maximum Data Center Efficiency

The Emulex HBAnyware enterprise-class management application has gained broad market acceptance with over 6 million Fibre Channel and FCoE ports managed to date. Building on the success of the HBAnyware application, Emulex has released OneCommand Manager.

OneCommand Manager's multi-protocol, cross platform architecture, provides centralized management of Emulex HBAs and Universal Converged Networking Adapters (UCNAs) within the enterprise datacenter. OneCommand Manager streamlines IT administrative tasks by delivering uniform management across heterogeneous data center environments. To ensure a transparent transition for customers who are using Emulex's HBAnyware management solution, OneCommand Manager is backward compatible with HBAnyware 4.1.

Key Benefits

- Provides superior performance for the enterprise
- Integrates seamlessly into existing SANs
- Supports IT server consolidation and energy conservation initiatives
- Allows application of SAN best practices, tools and processes with virtual server deployments
- Protects sensitive data from unauthorized access
- Assures data availability and data integrity
- Improves IT staff productivity through simplified deployment and management

Key Features

- Support for Message Signaled Interrupts eXtended (MSI-X), improves host utilization & enhances application performance
- Support for 8Gb/s, 4Gb/s & 2Gb/s Fibre Channel devices
- Comprehensive virtualization capabilities with support for N_Port ID Virtualization (NPIV) and Virtual Fabric
- Host to Fabric FC-SP authentication
- Long wave optical transceiver model available—allows the board to transmit signal over long distances
- BlockGuard® ready—ensures end-to-end data integrity
- Common driver model allows a single driver to support all Emulex HBAs on a given OS
- Easy deployment of new firmware with minimal server reboots
- Efficient centralized administration of Emulex HBAs via powerful management tools
- PCIe 2.0 bus compliant, with PCIe 1.0 backward compatibility supported



LightPulse® LPe12000/LPe12002

8Gb/s Fibre Channel PCIe 2.0 Host Bus Adapter



SPECIFICATIONS

Standards

- ANSI Fibre Channel: FC-PI-4, FC-FS-2, FC-FS-2/AM1, FC-LS, FC-AL-2, FC-GS-6, FC-FLA, FC-PLDA, FC-TAPE, FC-DA, FCP through FCP-4, SBC-3, FC-SP, FC-HBA and SMI-S v1.1
- PCI Express base spec 2.0
- PCI Express card electromechanical spec 2.0
- Fibre Channel class 2 and 3
- PHP hot plug-hot swap

Architecture

- Single-channel (LPe12000) or dual-channel (LPe12002)
- 8Gb/s, 4Gb/s or 2Gb/s FC Link speeds automatically detected
- Integrated data buffer and code space memory

Comprehensive OS Support

- Windows, Linux, NetWare, Solaris, VMware
- Additional support is available from OEMs and partners

Hardware Environments

- PowerPC®, SPARC®, x86, x64 and Intel® Itanium® 64-bit processor family

Optical

- Data rates: 2.125, 4.25 and 8.5Gb/s (auto-detected)
- Optics: Short wave lasers with LC type connector
- Cable: Operating at 8Gb/s
 - 50/125µm (500MHz*km BW)-up to 50m
 - 50/125µm (2000MHz*km BW)-up to 150m

Physical Dimensions

- Short, low profile MD2 form factor card
- 167.64mm x 68.91mm (6.60" x 2.71")
- Standard bracket (low profile available)

Power & Environmental Requirements

- Volts: +3.3, +12
- Operating temperature: 0° to 55° C (32° to 131° F)
- Storage temperature: -40° to 70° C (-40° to 158° F)
- Relative humidity: 5% to 95% non-condensing
- 23 degree C wet bulb

Agency Approvals

- Class 1 Laser Product per DHHS 21CFR (J) and EN60825-1
- UL recognized to UL 60950-1
- CUR recognized to CSA22.2, No. 60950-1-03
- Baurt-certified to EN60950-1
- FCC Rules, Part 15, Class A
- ICES-003, Class A
- EMC Directive 2004/108/EEC (CE Mark)
 - EN55022, Class A
 - EN55024
- Australian EMC Framework (C-Tick Mark)
 - AS/NZS CISPR22, Class A
- VCCI (Japan), Class A
- MIC (Korea), Class A
- BSMI (Taiwan), Class A
- EU RoHS Compliant (Directive 2002/95/EC)
- China RoHS Compliant

Ordering Information

- **LPe12000-M8**
 - Single-channel, multi-mode optic interface
- **LPe12002-M8**
 - Dual-channel, multi-mode optic interface
- **LPe12002-X8**
 - Dual-channel, single-mode optic interface
 - Long wave optical transceivers – allows the board to transmit a signal up to 1.4km when using 800-SM-LC-I, or up to 10km when using 800-SM-LC-L
- **LPe12100-OPT**
 - Emulex Certified Spare Optic Kit for LightPulse 8Gb/s Fibre Channel HBAs
 - QTY 1, 8Gb/s short wave lasers with LC-type connector SFP+ optic
 - Compatible with all Emulex LightPulse 8Gb/s Fibre Channel Host Bus Adapters
 - For use as an on-site spare optic

Additional Features

Performance features

- Doubling the maximum Fibre Channel link rate from 4Gb/s to 8Gb/s and enhanced virtualization capabilities help support IT “Green” initiatives
- Frame-level Multiplexing and out-of-order frame reassembly increases link efficiency and maximizes HBA performance.

Data protection features

- End-to-end data protection with hardware parity, CRC, ECC and other advanced error checking and correcting algorithms ensure data is safe from corruption.

Deployment and management features

- Universal Boot capability allows the appropriate boot environment to be automatically selected for any given hardware.
- Boot from SAN capability reduces system management costs and increases uptime.
- Detailed real-time event logging and tracing enables quick diagnosis of SAN problems.
- Beaconing feature flashes the HBA LEDs, simplifying their identification within server racks.
- Environmental monitoring feature helps to optimize SAN availability.

Management Features

- The Emulex AutoPilot Installer automates the HBA installation process and significantly reduces time to deployment and administrative costs. Automated installation and configuration of driver and management tools simplifies deployment of multiple adapters within Windows environments. A single installation of driver and management application eliminates multiple reboots and ensures that each component is installed correctly and the HBA is ready to use.
- The Emulex OneCommand™ Manager application enables centralized discovery, monitoring, reporting, and administration of Emulex HBAs and UCNAs on local and remote hosts. Powerful automation capabilities facilitate remote driver parameter, firmware and boot code upgrades. Advanced diagnostic features such as adapter port beaconing and adapter statistics help to optimize management and network performance while the environmental monitoring feature helps to maintain optimum host to fabric connections. In addition to the GUI interface, management functions can also be performed via a scriptable Command Line Interface (CLI) as well as a web browser. With in-band and out-of-band management capabilities, Emulex provides data center administrators with the greatest level of management flexibility.
- Emulex’s management instrumentation complies to Open Management Standards, such as SMI-S and common HBA API support, which enables seamless upward integration into enterprise storage and server management solutions.



www.emulex.com

World Headquarters 3333 Susan Street, Costa Mesa, CA 92626 +1 714 662 5600
Wokingham, UK +44 (0) 118 977 2929 | **Munich, Germany** +49 (0) 89 97007 177
Paris, France +33 (0) 158 580 022 | **Beijing, China** +86 10 68499547
Tokyo, Japan +81 3 5325 3261 | **Bangalore, India** +91 80 40156789

Emulex Connects™ Servers, Storage and People

twitter.com/emulex [friendfeed.com/emulex](https://www.facebook.com/emulex) [bit.ly/emulexlinks](https://www.linkedin.com/company/emulex) [bit.ly/emulexfb](https://www.youtube.com/emulex)

©2012 Emulex, Inc. All rights reserved. This document refers to various companies and products by their trade names. In most, if not all cases, their respective companies claim these designations as trademarks or registered trademarks. This information is provided for reference only. Although this information is believed to be accurate and reliable at the time of publication, Emulex assumes no responsibility for errors or omissions. Emulex reserves the right to make changes or corrections without notice. This report is the property of Emulex and may not be duplicated without permission from the Company.